

K-LKM S NW7,8 IG

Safety couplings DN 7.8, female

Свойства

Работно налягане	макс. 20 bar
протичане въздух	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
температура на средата	-20 °C to +100 °C
съединение корпус на клапана	Nickel-plated brass
пружина, сачми	Stainless-steel
плъзгаща се втулка	Anodised aluminium
деблокираща втулка	Hardened and nickel-plated steel
уплътняващ материал	NBR



Указание

Други данни при запитване.

Описание

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Артикул

Обозначение	Съединение	Дължина (mm)	SW (mm)
K- 07 35 08 85	G 1/4 female	75,0	19
K- 07 35 08 86	G 3/8 female	75,0	19
K- 07 35 08 87	G 1/2 female	80,0	24

Допълнителни елементи

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass