

# K-RD STUECKE POM

Reducers

**HANSA FLEX**

## Свойства

|                     |   |
|---------------------|---|
| работно налягане    | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)    |
| работна температура | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| Материал            | Acetalpolymerisat (POM)                           |
| уплътняващ материал | NBR   |



## Указание

Други данни при запитване.

## Описание

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

## Артикул

| Обозначение    | за външен Ø на маркуча | L1<br>(mm) | щуцер<br>(mm) |
|----------------|------------------------|------------|---------------|
| K- 07 40 28 91 | 8 mm                   | 46,7       | 12            |
| K- 07 40 28 92 | 10 mm                  | 50,9       | 12            |
| K- 07 40 28 93 | 10 mm                  | 61,2       | 15            |
| K- 07 40 28 94 | 12 mm                  | 61,2       | 15            |
| K- 07 40 28 95 | 15 mm                  | 71,7       | 18            |
| K- 07 40 28 96 | 15 mm                  | 72,7       | 22            |
| K- 07 40 28 97 | 18 mm                  | 71,8       | 22            |
| K- 07 40 28 98 | 15 mm                  | 81,4       | 28            |
| K- 07 40 28 99 | 22 mm                  | 82,6       | 28            |