

K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring

HANSA FLEX

Свойства

Течности	Air, neutral gases (filtered)
работно налягане	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
работна температура	-20 °C to +50 °C
Съединение 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
съединение 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
електрическо съединение	Plug connector PG 9
Съдържа се в обема на доставката	Plug connector PG 9, conversion plate, screws and seal
консумирана енергия	3 W=5 VA~
корпус	Anodised aluminium
шибър	Stainless steel
уплътняващ материал	NBR



Указание

Други данни при запитване.

Описание

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Артикул

Обозначение	Напрежение	Port 1	съединение 3 + 5	DN	протичане (L/min)
K- 07 15 00 13	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 14	24 V DC	G 1/4	G 1/4	7	1250