

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

HANSA FLEX

Свойства

| | |
|-----------------------|---------------------------|
| работно налягане | Max. 50 bar |
| повърхност | Hot dip galvanised |
| присъединителна резба | acc. ISO 7-1 |
| Материал | Zinc plated steel ST 37-2 |



Указание

Други данни при запитване.

Описание

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Артикул

| Обозначение | Резба | Дължина (mm) |
|----------------|-------|--------------|
| K- 07 40 35 71 | R 1/4 | 40,0 |
| K- 07 40 35 72 | R 1/4 | 60,0 |
| K- 07 40 35 73 | R 1/4 | 80,0 |
| K- 07 40 35 66 | R 1/4 | 100,0 |
| K- 07 40 35 67 | R 1/4 | 120,0 |
| K- 07 40 35 68 | R 1/4 | 150,0 |
| K- 07 40 35 69 | R 1/4 | 180,0 |
| K- 07 40 35 70 | R 1/4 | 200,0 |
| K- 07 40 35 95 | R 3/8 | 40,0 |
| K- 07 40 35 96 | R 3/8 | 60,0 |
| K- 07 40 35 97 | R 3/8 | 80,0 |
| K- 07 40 35 90 | R 3/8 | 100,0 |
| K- 07 40 35 91 | R 3/8 | 120,0 |
| K- 07 40 35 92 | R 3/8 | 150,0 |
| K- 07 40 35 93 | R 3/8 | 180,0 |
| K- 07 40 35 94 | R 3/8 | 200,0 |
| K- 07 40 35 63 | R 1/2 | 40,0 |
| K- 07 40 35 64 | R 1/2 | 60,0 |
| K- 07 40 35 65 | R 1/2 | 80,0 |
| K- 07 40 35 58 | R 1/2 | 100,0 |
| K- 07 40 35 59 | R 1/2 | 120,0 |
| K- 07 40 35 60 | R 1/2 | 150,0 |
| K- 07 40 35 61 | R 1/2 | 180,0 |
| K- 07 40 35 62 | R 1/2 | 200,0 |
| K- 07 40 35 87 | R 3/4 | 40,0 |
| K- 07 40 35 88 | R 3/4 | 60,0 |
| K- 07 40 35 89 | R 3/4 | 80,0 |
| K- 07 40 35 82 | R 3/4 | 100,0 |
| K- 07 40 35 83 | R 3/4 | 120,0 |
| K- 07 40 35 84 | R 3/4 | 150,0 |
| K- 07 40 35 85 | R 3/4 | 180,0 |
| K- 07 40 35 86 | R 3/4 | 200,0 |
| K- 07 40 35 39 | R 1 | 40,0 |
| K- 07 40 35 40 | R 1 | 60,0 |
| K- 07 40 35 41 | R 1 | 80,0 |
| K- 07 40 35 34 | R 1 | 100,0 |
| K- 07 40 35 35 | R 1 | 120,0 |
| K- 07 40 35 36 | R 1 | 150,0 |



Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържанието на данни.

23.06.2024

HANSA-FLEX AG

www.hansa-flex.com

1

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

HANSA FLEX

Артикул

| Обозначение | Резба | Дължина (mm) |
|----------------|---------|-----------------|
| K- 07 40 35 37 | R 1 | 180,0 |
| K- 07 40 35 38 | R 1 | 200,0 |
| K- 07 40 35 55 | R 1 1/4 | 40,0 |
| K- 07 40 35 56 | R 1 1/4 | 60,0 |
| K- 07 40 35 57 | R 1 1/4 | 80,0 |
| K- 07 40 35 50 | R 1 1/4 | 100,0 |
| K- 07 40 35 51 | R 1 1/4 | 120,0 |
| K- 07 40 35 52 | R 1 1/4 | 150,0 |
| K- 07 40 35 53 | R 1 1/4 | 180,0 |
| K- 07 40 35 54 | R 1 1/4 | 200,0 |
| K- 07 40 35 47 | R 1 1/2 | 40,0 |
| K- 07 40 35 48 | R 1 1/2 | 60,0 |
| K- 07 40 35 49 | R 1 1/2 | 80,0 |
| K- 07 40 35 42 | R 1 1/2 | 100,0 |
| K- 07 40 35 43 | R 1 1/2 | 120,0 |
| K- 07 40 35 44 | R 1 1/2 | 150,0 |
| K- 07 40 35 45 | R 1 1/2 | 180,0 |
| K- 07 40 35 46 | R 1 1/2 | 200,0 |
| K- 07 40 35 79 | R 2 | 40,0 |
| K- 07 40 35 80 | R 2 | 60,0 |
| K- 07 40 35 81 | R 2 | 80,0 |
| K- 07 40 35 74 | R 2 | 100,0 |
| K- 07 40 35 75 | R 2 | 120,0 |
| K- 07 40 35 76 | R 2 | 150,0 |
| K- 07 40 35 77 | R 2 | 180,0 |
| K- 07 40 35 78 | R 2 | 200,0 |
| K- 07 40 50 93 | R 2 1/2 | 80,0 |
| K- 07 40 50 88 | R 2 1/2 | 100,0 |
| K- 07 40 50 89 | R 2 1/2 | 120,0 |
| K- 07 40 50 90 | R 2 1/2 | 150,0 |
| K- 07 40 50 91 | R 2 1/2 | 180,0 |
| K- 07 40 50 92 | R 2 1/2 | 200,0 |
| K- 07 40 50 99 | R 3 | 80,0 |
| K- 07 40 50 94 | R 3 | 100,0 |
| K- 07 40 50 95 | R 3 | 120,0 |
| K- 07 40 50 96 | R 3 | 150,0 |
| K- 07 40 50 97 | R 3 | 180,0 |
| K- 07 40 50 98 | R 3 | 200,0 |