

K-GMM 2

Glycerine-filled pressure gauges, CrNi steel type

HANSA FLEX

Свойства

тип	233.30
Изпълнение	Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Приложение	For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere
клас качество	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
температура на средата	max. +100 °C
околна температура	-20 °C до +60 °C
корпус	CrNi steel
зрително стъкло	Laminated safety glass Ø 63 = Polycarbonate



Указание

Други данни при запитване.

Артикул

Обозначение	Диапазон на измерване	Ø (mm)	Съединение
K- 07 20 07 03	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 04	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 07 05	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 07 06	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 07 07	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 07 08	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 07 09	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 07 10	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 07 11	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 07 12	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 07 13	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 07 14	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 01 79	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 80	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 01 81	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 01 82	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 01 83	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 01 84	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 85	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 86	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 87	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 88	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 89	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 90	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 91	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 01 92	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 01 93	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 94	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 01 95	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 01 96	0 - 600.0 bar	100,0	G 1/2"