

# K-GMM 2

Glycerine-filled pressure gauges, CrNi steel type

**HANSA FLEX**

## Свойства

|                        |  |
|------------------------|--|
| тип                    | 233.30   |
| Изпълнение             | Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)    |
| Приложение             | For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere |
| клас качество          | 1,6 (Ø 63 mm), 1,0 (Ø 100 mm)  |
| температура на средата | max. +100 °C   |
| околна температура     | -20 °C до +60 °C   |
| корпус                 | CrNi steel   |
| зрително стъкло        | Laminated safety glass Ø 63 = Polycarbonate  |



## Указание

Други данни при запитване.

## Артикул

| Обозначение    | Диапазон на измерване | Ø (mm) | Съединение |
|----------------|-----------------------|--------|------------|
| K- 07 20 07 03 | -1 / 0.0 bar          | 63,0   | G 1/4"     |
| K- 07 20 07 04 | 0 - 4.0 bar           | 63,0   | G 1/4"     |
| K- 07 20 07 05 | 0 - 6.0 bar           | 63,0   | G 1/4"     |
| K- 07 20 07 06 | 0 - 10.0 bar          | 63,0   | G 1/4"     |
| K- 07 20 07 07 | 0 - 16.0 bar          | 63,0   | G 1/4"     |
| K- 07 20 07 08 | 0 - 25.0 bar          | 63,0   | G 1/4"     |
| K- 07 20 07 09 | 0 - 40.0 bar          | 63,0   | G 1/4"     |
| K- 07 20 07 10 | 0 - 60.0 bar          | 63,0   | G 1/4"     |
| K- 07 20 07 11 | 0 - 100.0 bar         | 63,0   | G 1/4"     |
| K- 07 20 07 12 | 0 - 160.0 bar         | 63,0   | G 1/4"     |
| K- 07 20 07 13 | 0 - 250.0 bar         | 63,0   | G 1/4"     |
| K- 07 20 07 14 | 0 - 400.0 bar         | 63,0   | G 1/4"     |
| K- 07 20 01 79 | -1 / 0.0 bar          | 100,0  | G 1/2"     |
| K- 07 20 01 80 | -1 / +1.5 bar         | 100,0  | G 1/2"     |
| K- 07 20 01 81 | -1 / +3.0 bar         | 100,0  | G 1/2"     |
| K- 07 20 01 82 | -1 / +5.0 bar         | 100,0  | G 1/2"     |
| K- 07 20 01 83 | -1 / +9.0 bar         | 100,0  | G 1/2"     |
| K- 07 20 01 84 | 0 - 2.5 bar           | 100,0  | G 1/2"     |
| K- 07 20 01 85 | 0 - 4.0 bar           | 100,0  | G 1/2"     |
| K- 07 20 01 86 | 0 - 6.0 bar           | 100,0  | G 1/2"     |
| K- 07 20 01 87 | 0 - 10.0 bar          | 100,0  | G 1/2"     |
| K- 07 20 01 88 | 0 - 16.0 bar          | 100,0  | G 1/2"     |
| K- 07 20 01 89 | 0 - 25.0 bar          | 100,0  | G 1/2"     |
| K- 07 20 01 90 | 0 - 40.0 bar          | 100,0  | G 1/2"     |
| K- 07 20 01 91 | 0 - 60.0 bar          | 100,0  | G 1/2"     |
| K- 07 20 01 92 | 0 - 100.0 bar         | 100,0  | G 1/2"     |
| K- 07 20 01 93 | 0 - 160.0 bar         | 100,0  | G 1/2"     |
| K- 07 20 01 94 | 0 - 250.0 bar         | 100,0  | G 1/2"     |
| K- 07 20 01 95 | 0 - 400.0 bar         | 100,0  | G 1/2"     |
| K- 07 20 01 96 | 0 - 600.0 bar         | 100,0  | G 1/2"     |