K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type



Свойства			
Работно налягане	макс. 10 bar		
протичане въздух	1.800 l/min (at 6 bar and Δp = 1 bar)		
температура на средата	-20 °C to +150 °C		
корпус	Stainless steel 1.4404		
резба	Stainless steel 1.4404		
вътрешни части	Stainless steel 1.4404		
копче, клапан	Stainless steel 1.4404		
уплътняващ материал	FKM		



Указание

Not suitable for hitting / pulsating tools.

Други данни при запитване.

Описание

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Допълнителна информация

Not suitable for hitting / pulsating tools.

Артикул			
Обозначение	Съединение	Дължина _(mm)	SW (mm)
K- 07 35 12 79	G 1/4 female	71,5	21
K- 07 35 12 80	G 3/8 female	75,5	21
K- 07 35 12 81	G 1/2 female	77,5	24