

# K-LKM S NW7,2 AG

Safety couplings DN 7.2, male

**HANSA FLEX**

## Свойства

Работно налягане	0 - 35 bar, maximum static working pressure (non-pulsating)
протичане въздух	1.100 l/min (at $\Delta p = 0.5$ bar)
температура на средата	-30 °C to +100 °C
корпус, втулка, корпус на клапан	Nickel-plated brass
пружина, сачми	Stainless-steel
уплътняващ материал	NBR



## Указание

Други данни при запитване.

## Описание

One-hand safety coupling with double locking mechanism. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

## Артикул

Обозначение	Съединение	Дължина (mm)	SW (mm)
K- 07 35 02 92	G 1/4 male	44,0	22
K- 07 35 02 93	G 3/8 male	44,0	22
K- 07 35 02 94	G 1/2 male	47,0	24

## Допълнителни елементи

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,