K-DMUF FESTSTOFFHALTIGE MED

Pressure transmitter for viscous and solids-containing media, nonlinearity 0.2%

Свойства

тип	S-11
напрежение	DC 10 (14) ... 30 V
електрическо съединение	With right-angle connector acc. to DIN EN 175301-803 A
вид защита	IP 65 acc. to EN 60529
изходящ сигнал	4 to 20 mA, 2-wire
нелинейност	0.2% of span
температура на средата	-30 °C to +100 °C; (Range: 400 and 600 bar: -30 °C to +70 °C)
околна температура	-20 °C to +80 °C
части в допир с измерваното вещество	CrNi steel 1.4571
корпус	CrNi steel 1.4571



Описание

Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

Допълнителна информация

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Артикул

Обозначение	Диапазон на измерване	Резба
K- 07 20 12 38	0 - 0.25 bar	G 1
K- 07 20 12 39	0 - 0.4 bar	G 1
K- 07 20 12 40	0 - 1.0 bar	G 1
K- 07 20 12 41	0 - 10.0 bar	G 1/2
K- 07 20 12 42	0 - 100.0 bar	G 1/2
K- 07 20 12 43	0 - 16.0 bar	G 1/2
K- 07 20 12 44	0 - 160.0 bar	G 1/2
K- 07 20 12 45	0 - 25.0 bar	G 1/2
K- 07 20 12 46	0 - 250.0 bar	G 1/2
K- 07 20 12 47	0 - 4.0 bar	G 1/2
K- 07 20 12 48	0 - 40.0 bar	G 1/2
K- 07 20 12 49	0 - 400.0 bar	G 1/2
K- 07 20 12 50	0 - 6.0 bar	G 1/2
K- 07 20 12 51	0 - 60.0 bar	G 1/2
K- 07 20 12 52	0 - 600.0 bar	G 1/2

Резервни части

K-ZUBEH DRUCKMESSUMFOR	Accessoires for pressure transmitters for viscous and solids-containing media, nonlinearity 0.2%

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.