

# K-WERKST-SCHLAUCH SOFT

Workshop hose soft

**HANSA FLEX**

## Свойства

Вътрешен слой	Soft-PVC, black
Подложка	полиестерна оплетка
Външен слой	Soft-PVC, blue
температура	-20 °C to +60 °C
дължина на ролката	50 m



## Указание

Други данни при запитване.

## Описание

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

## Артикул

Обозначение	Ø маркуч отвътре (mm)	Ø маркуч отвън (mm)	Max. working pressure resistance at 23°C (bar)	Радиус на огъване мин. (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88