K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

Свойства

вид съединение	with pushbutton safety coupling NW 7,4 steel nipple galvanised
работна температура	-40 °C to +74 °C



Указание

Други данни при запитване.

Описание

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.
Не е подходящо за биещи или пулсиращи инструменти!

Артикул

Обозначение	Ø маркуч отвътре (mm)	Ø маркуч отвън (mm)	Ø външна навивка (mm)	Max. working pressure resistance at 23°C (bar)	макс. работна дължина (m)
K- 07 10 12 71	5,0	8,0	40	10	3,0
K- 07 10 12 73	5,0	8,0	40	10	6,0
K- 07 10 12 75	5,0	8,0	40	10	7,5
K- 07 10 12 80	6,3	9,5	60	10	3,0
K- 07 10 12 82	6,3	9,5	60	10	6,0
K- 07 10 12 84	6,3	9,5	60	10	7,5
K- 07 10 12 78	6,3	9,5	60	10	10,0
K- 07 10 12 89	8,0	12,0	80	9	3,0
K- 07 10 12 91	8,0	12,0	80	9	6,0
K- 07 10 12 93	8,0	12,0	80	9	7,5
K- 07 10 12 87	8,0	12,0	80	9	10,0

Принадлежности

K-DREHBARE VERSCHRAUBUNG	Swivel adapters

Въпреки най-старателната проверка не са изключени грешки и ние не поемаме гаранция за съдържащите се данни.