

K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

HANSA FLEX

Свойства

| | |
|--------------------|--------------------------------|
| Вътрешен слой | Soft-PVC, red, oil resistant |
| Подложка | полиестерна оплетка |
| Външен слой | Soft-PVC, black, oil resistant |
| температура | -20 °C to +60 °C |
| дължина на ролката | 50 m |



Указание

Други данни при запитване.

Описание

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

Артикул

| Обозначение | Ø маркуч отвътре (mm) | Ø маркуч отвън (mm) | Max. working pressure resistance at 23°C (bar) | Радиус на огъване мин. (mm) |
|----------------|-----------------------|---------------------|--|-----------------------------|
| K- 07 10 10 41 | 6,3 | 11,0 | 16 | 18 |
| K- 07 10 10 42 | 8,0 | 13,0 | 16 | 25 |
| K- 07 10 10 43 | 9,0 | 14,5 | 16 | 25 |
| K- 07 10 10 44 | 10,0 | 15,5 | 16 | 35 |
| K- 07 10 10 45 | 12,7 | 19,0 | 16 | 50 |
| K- 07 10 10 46 | 16,0 | 23,0 | 16 | 70 |
| K- 07 10 10 47 | 19,0 | 26,5 | 16 | 70 |
| K- 07 10 10 48 | 25,0 | 33,5 | 16 | 120 |