

K-DIGIT DRUCKSCHA H 3DURCHF IA PF2A

Digital Flow Switch PF2A

HANSA FLEX

Свойства

Конструкция	Digital Flow Switch
макс. работно налягане	0,1 MPa
номинално напрежение	24 V DC
работна индикация	3 digits, 7-Segment-LED lights at output signal = ON: OUT1: green, OUT2: red)
I/O кабел	without connection cable
вид защита	IP 65
температура на средата	0 °C to +50 °C
околна температура	0 °C to +50 °C
Течности	Air and nitrogen
серия	PF2A
Други данни	for High flow Integrated Display Type



Описание

Digital flow switch for high flow, series PF2A, for air and nitrogen, with integrated display unit, measuring range 150 to 3000 l/min, smallest adjustment unit 5 l/min, media temperature 0 to 50 °C, operating temperature range 0 to 50 °C, repetition accuracy max. ±3% of the measuring range, temperature characteristic max. ±2% of the measuring range. (0 to 50 °C, based on 25 °C), current consumption max. 150 mA, measuring principle thermistor (heating element), operating display 3-digit, 7-segment LED (illuminates at output signal ON OUT1: Green OUT2: Red), operating pressure range 0.1 to 1.5 MPa, switch output PNP open collector 1 output and 1 analogue output (1 to 5 V), with function to switch over the display unit, supply voltage 24 V DC, protection class IP 65, connection cable not included, connection size G 1 1/2

Артикул

Обозначение	Присъединителна резба	изходящ сигнал	единица за настройка [Мин] (L/min)	Диапазон на измерване	мин. работно налягане (MPa)	Номинално напрежение/ вид ток	разход на електроенергия max. (mA)	точност при възпроизвеждане
K-07 50 00 28	G 1	PNP + Analog output (1-5V)	5,00	150 bis 3000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K-07 50 00 29	G 1	PNP + Analog output (4-20mA)	5,00	150 bis 3000 l/min	1,50	-	150	max. ±3 % from scale
K-07 50 00 31	G 1 1/2	PNP + Analog output (1-5V)	10,00	300 bis 6000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K-07 50 00 32	G 1 1/2	PNP + Analog output (4-20mA)	10,00	300 bis 6000 l/min	1,50	-	150	max. ±3 % from scale
K-07 50 00 36	G 2	PNP + Analog output (1-5V)	10,00	600 bis 12000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K-07 50 00 37	G 2	PNP + Analog output (4-20mA)	10,00	600 bis 12000 l/min	1,50	-	150	max. ±3 % from scale