

K-STOSSDAEMPFER RB

Shock absorber RB

HANSA FLEX

Свойства

серия RB

Други данни high power density through hydraulic function principle results in min.. size
Impact speed up to max. 5 m / sec.
Annular surface at the front side can be used as a mechanical stop



Описание

Shock absorber, series RB, high power density from hydraulic design principle results in min. dimensions, impact speed up to max. 5 m/sec., the annulus on the end can be used as a mechanical stop, basic version, thread M 8 x 1, stroke 6 mm

Артикул

| Обозначение | Такт (mm) | Изпълнение | дефиниция | Резба |
|----------------|-----------|-------------|----------------|------------|
| K- 07 55 02 24 | 5 | basic model | Shock absorber | M 8 x 1 |
| K- 07 55 02 25 | 6 | basic model | Shock absorber | M 8 x 1 |
| K- 07 55 02 27 | 6 | basic model | Shock absorber | M 10 x 1 |
| K- 07 55 02 28 | 7 | basic model | Shock absorber | M 10 x 1 |
| K- 07 55 02 30 | 11 | basic model | Shock absorber | M 14 x 1,5 |
| K- 07 55 02 31 | 12 | basic model | Shock absorber | M 14 x 1,5 |
| K- 07 55 02 33 | 15 | basic model | Shock absorber | M 20 x 1,5 |
| K- 07 55 02 35 | 25 | basic model | Shock absorber | M 27 x 1,5 |