

# K-W90 DRV AS-FS

Speed controllers, 90°, connection plug, with built-in indicator

**HANSA FLEX**

| Свойства                        |   |
|---------------------------------|---|
| макс. работно налягане          | 1 MPa   |
| мин. работно налягане           | 0.10 MPa  |
| изпускания                      | 1   |
| брой захранващи кабели          | 1   |
| изложение прозорец за индикация | 0°  |
| цвет въртящо се копче           | Blue  |
| Контролно налягане              | 1,50 MPa  |
| управление                      | Flow governing  |
| температура на средата          | -5 °C to +60 °C (ohne Gefrieren)  |
| околна температура              | -5 °C bis +60 °C (no freezing)  |
| Течности                        | въздух под налягане   |
| Материал на маркучка            | polyamid, soft polyamid, polyurethane, FEP, PFA   |
| серия                           | AS-FS   |
| Други данни                     | large rotary knob with push-lock latch<br>larger free space under the hose<br>Lockable rotary knob, numeric display |



| Артикул        |                      |                        |                            |                           |                      |                 |
|----------------|----------------------|------------------------|----------------------------|---------------------------|----------------------|-----------------|
| Обозначение    | Конструктивен размер | съединение изпускане   | съединение захранващ кабел | Изпълнение                | завъртания на иглата | Тегло за м (kg) |
| K- 07 30 30 54 | 1                    | for hose outer-Ø2 mm   | outer thread M 5           | with sealing ring         | 8                    | 0,007           |
| K- 07 30 30 57 | 1                    | for hose outer-Ø3.2 mm | outer thread M 5           | with sealing ring         | 8                    | 0,007           |
| K- 07 30 30 55 | 1                    | for hose outer-Ø4 mm   | outer thread M 5           | with sealing ring         | 8                    | 0,007           |
| K- 07 30 30 56 | 1                    | for hose outer-Ø6 mm   | outer thread M 5           | with sealing ring         | 8                    | 0,008           |
| K- 07 30 30 62 | 2                    | for hose outer-Ø3.2 mm | outer thread R 1/8         | Teflon coated             | 10                   | 0,007           |
| K- 07 30 30 67 | 2                    | for hose outer-Ø3.2 mm | outer thread R 1/4         | Teflon coated             | 10                   | 0,023           |
| K- 07 30 30 58 | 2                    | for hose outer-Ø4 mm   | outer thread R 1/8         | Teflon coated             | 10                   | 0,013           |
| K- 07 30 30 63 | 2                    | for hose outer-Ø4 mm   | outer thread R 1/4         | Teflon coated             | 10                   | 0,023           |
| K- 07 30 30 59 | 2                    | for hose outer-Ø6 mm   | outer thread R 1/8         | Teflon coated             | 10                   | 0,014           |
| K- 07 30 30 68 | 2                    | for hose outer-Ø6 mm   | outer thread G 1/8         | surface with sealing ring | 10                   | 0,014           |
| K- 07 30 30 64 | 2                    | for hose outer-Ø6 mm   | outer thread R 1/4         | Teflon coated             | 10                   | 0,023           |
| K- 07 30 30 69 | 2                    | for hose outer-Ø6 mm   | outer thread G 1/4         | surface with sealing ring | 10                   | 0,023           |
| K- 07 30 30 60 | 2                    | for hose outer-Ø8 mm   | outer thread R 1/8         | Teflon coated             | 10                   | 0,015           |
| K- 07 30 30 65 | 2                    | for hose outer-Ø8 mm   | outer thread R 1/4         | Teflon coated             | 10                   | 0,024           |
| K- 07 30 30 70 | 2                    | for hose outer-Ø8 mm   | outer thread G 1/4         | surface with sealing ring | 10                   | 0,024           |
| K- 07 30 30 61 | 2                    | for hose outer-Ø10 mm  | outer thread R 1/8         | Teflon coated             | 10                   | 0,016           |
| K- 07 30 30 66 | 2                    | for hose outer-Ø10 mm  | outer thread R 1/4         | Teflon coated             | 10                   | 0,025           |
| K- 07 30 30 71 | 2                    | for hose outer-Ø10 mm  | outer thread G 1/4         | surface with sealing ring | 10                   | 0,025           |
| K- 07 30 30 72 | 3                    | for hose outer-Ø6 mm   | outer thread R 3/8         | Teflon coated             | 10                   | 0,038           |
| K- 07 30 30 76 | 3                    | for hose outer-Ø6 mm   | outer thread G 3/8         | surface with sealing ring | 10                   | 0,038           |
| K- 07 30 30 73 | 3                    | for hose outer-Ø8 mm   | outer thread R 3/8         | Teflon coated             | 10                   | 0,038           |
| K- 07 30 30 77 | 3                    | for hose outer-Ø8 mm   | outer thread G 3/8         | surface with sealing ring | 10                   | 0,038           |
| K- 07 30 30 74 | 3                    | for hose outer-Ø10 mm  | outer thread R 3/8         | Teflon coated             | 10                   | 0,029           |
| K- 07 30 30 78 | 3                    | for hose outer-Ø10 mm  | outer thread G 3/8         | surface with sealing ring | 10                   | 0,029           |
| K- 07 30 30 75 | 3                    | for hose outer-Ø12 mm  | outer thread R 3/8         | Teflon coated             | 10                   | 0,041           |
| K- 07 30 30 79 | 4                    | for hose outer-Ø10 mm  | outer thread R 1/2         | Teflon coated             | 10                   | 0,062           |
| K- 07 30 30 82 | 4                    | for hose outer-Ø10 mm  | outer thread G 1/2         | surface with sealing ring | 10                   | 0,062           |
| K- 07 30 30 80 | 4                    | for hose outer-Ø12 mm  | outer thread R 1/2         | Teflon coated             | 10                   | 0,064           |
| K- 07 30 30 83 | 4                    | for hose outer-Ø12 mm  | outer thread G 1/2         | surface with sealing ring | 10                   | 0,064           |
| K- 07 30 30 81 | 4                    | for hose outer-Ø16 mm  | outer thread R 1/2         | Teflon coated             | 10                   | 0,068           |
| K- 07 30 30 84 | 4                    | for hose outer-Ø16 mm  | outer thread G 1/2         | surface with sealing ring | 10                   | 0,068           |