

### Vlastnosti

|                          |                     |
|--------------------------|---------------------|
| <b>Přípoj 1</b>          | Vnitřní závit BSP   |
| <b>Konstrukce</b>        | Přesuvná matice     |
| <b>Norma</b>             | ISO 8434-6          |
| <b>Materiál</b>          | Ocel                |
| <b>Povrchová ochrana</b> | galvanicky potažený |



### Výrobek

| Označení         | G1           | L1<br>(mm) | S1 |
|------------------|--------------|------------|----|
| <b>UEM AB 02</b> | G 1/8" -28   | 15,0       | 14 |
| <b>UEM AB 04</b> | G 1/4" -19   | 15,0       | 17 |
| <b>UEM AB 06</b> | G 3/8" -19   | 18,0       | 22 |
| <b>UEM AB 08</b> | G 1/2" -14   | 20,0       | 27 |
| <b>UEM AB 10</b> | G 5/8" -14   | 23,0       | 27 |
| <b>UEM AB 12</b> | G 3/4" -14   | 23,0       | 32 |
| <b>UEM AB 16</b> | G 1" -11     | 26,0       | 41 |
| <b>UEM AB 20</b> | G 1.1/4" -11 | 28,0       | 50 |
| <b>UEM AB 24</b> | G 1.1/2" -11 | 32,5       | 60 |

SW, S1, S2 = otvor klíče