

K-RMM U KUNSTSTOFF MZ

Standard pressure gauges, connection radial on bottom

HANSA FLEX

Vlastnosti

Typ	111.10 (radial connector on bottom)
Provedení	Bourdon-tube pressure gauge in standard design
Použití	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Jakostní třída	1.6 (Art No. K-07200303, K-07403298 - K-07201188: 2.5)
Ručička pro nastavenou hodnotu	(for Ø 160 mm - red pointer on the scale) red pointer to the window. For measuring ranges 0...0,6 bar bis 0...60 bar
Teplota média	max. +60 °C
Teplota okolí	-20 °C až +60 °C
Pouzdro	Plastic
Materiál měřicího členu a ukazatele	Slitina mědi
Průhledové sklo	Transparent plastic



Upozornění

Další údaje na dotaz.

Výrobek

Označení	Rozsah měření	Ø (mm)	Přípoj
K- 07 20 03 03	-1200 / 0.0 mbar	100,0	G 1/2"
K- 07 20 03 04	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 03 05	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 03 06	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 03 07	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 03 08	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 03 09	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 02 84	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 02 85	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 02 86	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 02 87	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 88	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 89	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 90	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 91	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 92	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 93	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 11 86	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 11 87	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 11 88	0 - 160.0 bar	100,0	G 1/2"