

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Vlastnosti

Provozní teplota	-60 °C to +100 °C (PA 12)
Vlastnosti	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Délka trubky	3 m
Jednotka balení	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Materiál	Polyamid PA 12, hard (according to DIN 73378)



Upozornění

Operating pressure with 2.5 x overpressure safety!

Další údaje na dotaz.

Popis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Výrobek

Označení	Vnější Ø trubky (mm)	Vnitřní Ø trubky (mm)	Max. provozní tlak při 20 °C (bar)	Barva
K- 07 10 04 56	12	9	38	modrá
K- 07 10 04 58	12	9	38	černá
K- 07 10 04 60	15	12	25	modrá
K- 07 10 04 62	15	12	25	černá
K- 07 10 04 64	18	14	28	modrá
K- 07 10 04 66	18	14	28	černá
K- 07 10 04 68	22	18	22	modrá
K- 07 10 04 70	22	18	22	černá
K- 07 10 04 72	28	23	20	modrá
K- 07 10 04 74	28	23	20	černá