

# K-SPIR SCHL

Spiral hose, without fittings

## Vlastnosti

Použití	Air, gases, oils, greases, fuels, organic and inorganic substances
Provozní teplota	-40 °C to +100 °C



## Upozornění

Další údaje na dotaz.

## Popis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Výrobek

Označení	Ø hadice vnitřní (mm)	Ø hadice vnější (mm)	Ø spirály vnější (mm)	Vinutí	Max. working pressure resistance at 23°C (bar)	Max. pracovní délka (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

## Příslušenství

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector