

# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

**HANSA FLEX**

## Vlastnosti

Typ připojení with kink protector, swivel type

Provozní teplota -40 °C to +74 °C



## Upozornění

Další údaje na dotaz.

## Popis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Výrobek

Označení	Závít	Ø hadice vnitřní (mm)	Ø hadice vnější (mm)	Ø vnějšího vinutí (mm)	Max. working pressure resistance at 23°C (bar)	Max. pracovní délka (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

## Příslušenství

K-DREHBARE VERSCHRAUBUNG Swivel adapters