
# K-SPIR SCHL KUPPL SET

Spiral hose and coupling kits

## Vlastnosti

| | |
|---|---|
| **Provozní tlak** | max. 10 bar (to the temperature +20 °C); max. 7 bar (at temperature +40 °C); max. 5 bar (at temperature +60 °C) |
| **Spojka** | High quality hand quick release coupling of steel for high flow rates<br>For demanding applications with high mechanical wear |
| **Spirálová hadice** | Polyurethane |



## Upozornění

Další údaje na dotaz.

## Popis

For pneumatic applications in challenging industrial environments. High-quality, one-hand quick disconnect coupling made of steel with safety lock to prevent unintentional disconnection. For complex applications susceptible to severe mechanical wear. The outer layer of the hose, which is designed to withstand flying sparks and scorching, has special spark protection. It is therefore ideal for all pneumatic tools used in welding processes.

## Výrobek

| Označení | Rozměr hadice | Ø spirály (mm) | Pracovní délka (m) |
|---|---|---|---|
| **K- 07 10 07 56** | 10 mm x 6,5 mm | 52 | 4,0 |
| **K- 07 10 07 57** | 10 mm x 6,5 mm | 52 | 6,0 |
| **K- 07 10 07 58** | 12 mm x 8 mm | 65 | 8,0 |

*Navzdory nejpečlivější kontrole nemůžeme vyloučit chyby a nepřejímáme žádnou záruku za obsažené údaje.*