

Vlastnosti

Pouzdro	Amaplast with hinged cover
Zabudovaný do pouzdra	Hanging eyelets, wall mounting fixing and standing feet
Pojistka	Beneath transparent lid (4 MW)
Provedení	Pre-wired
Průchod pro vedení	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
Stupeň krytí	IP 44



Upozornění

Další údaje na dotaz.

Popis

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Výrobek

Označení	Osazení	Barva
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	žlutá
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	stříbro

Příslušenství

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«