

## Vlastnosti

<b>Pouzdro</b>	Amaplast with hinged cover
<b>Zabudovaný do pouzdra</b>	Hanging eyelets, wall mounting fixing and standing feet
<b>Pojistka</b>	Beneath transparent lid (4 MW)
<b>Provedení</b>	Pre-wired
<b>Průchod pro vedení</b>	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
<b>Stupeň krytí</b>	IP 44



## Upozornění

Další údaje na dotaz.

## Popis

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

## Výrobek

Označení	Osazení	Barva
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	žlutá
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	stříbro

## Příslušenství

<b>K-VT 2 KUPPL 7,2 STECKNIP MS</b>	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
<b>K-ZUBEH VSEH 3 KRAFT AIRKRAFT</b>	Accessories for receptacle combinations »3-Kraft« and »airkraft«