

Vlastnosti

| | |
|------------------------------|---|
| Pouzdro | Amaplast with hinged cover |
| Zabudovaný do pouzdra | Hanging eyelets, wall mounting fixing and standing feet |
| Pojistka | Beneath transparent lid (4 MW) |
| Provedení | Pre-wired |
| Průchod pro vedení | Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out) |
| Stupeň krytí | IP 44 |



Upozornění

Další údaje na dotaz.

Popis

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Výrobek

| Označení | Osazení | Barva |
|----------------|---|---------|
| K- 07 10 03 52 | 4 Schuko socket 16 A 2p + E 230 V | žlutá |
| K- 07 10 03 51 | 3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V | stříbro |

Příslušenství

| | |
|--------------------------------------|--|
| K-VT 2 KUPPL 7,2 STECKNIP MS | Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8 |
| K-ZUBEH VSEH 3 KRAFT AIRKRAFT | Accessories for receptacle combinations »3-Kraft« and »airkraft« |