

# K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

**HANSA FLEX**

## Vlastnosti

Teplota média	-5 °C to +80 °C
Max. vypínací tlak	16 bar
Spínací schopnost	5,5 kW
Typ kontaktu	NC (3-pole)
Max. četnost spínání	120 (electrical), 600 (mechanical)
Stupeň krytí	IP 54



## Upozornění

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Další údaje na dotaz.

## Popis

Three-phase version

## Upozornění k objednávkám

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Další informace

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## Výrobek

Označení	Připojení stlačeného vzduchu	Rozsah nastavení
K- 07 30 24 25	G 1/2	2,0 - 11,0 bar
K- 07 30 24 27	G 1/2	2,5 - 16,0 bar