

# K-SCHMUTZFAENGER VA

## Strainers

### Vlastnosti

|                  |                                   |
|------------------|-----------------------------------|
| Provozní tlak    | Max. 40 bar                       |
| Provozní teplota | max. 180 °C                       |
| Popis závitů     | G thread acc. to ISO 228-1        |
| Teplota média    | max. 180 °C                       |
| Sítová vložka    | Stainless steel, mesh size 0.6 mm |
| Pouzdro a hlava  | stainless steel 1.4401/1.4408     |



### Upozornění

Další údaje na dotaz.

### Výrobek

| Označení       | DN | Závit   | C<br>(mm) | L<br>(mm) | SW1<br>(mm) | SW2<br>(mm) |
|----------------|----|---------|-----------|-----------|-------------|-------------|
| K- 07 30 25 00 | 8  | G 1/4   | 47,0      | 65,0      | 26          | 19          |
| K- 07 30 25 01 | 10 | G 3/8   | 47,0      | 65,0      | 26          | 19          |
| K- 07 30 25 02 | 15 | G 1/2   | 47,0      | 65,0      | 26          | 19          |
| K- 07 30 25 03 | 20 | G 3/4   | 60,0      | 80,0      | 32          | 21          |
| K- 07 30 25 04 | 25 | G 1     | 71,0      | 90,0      | 41          | 27          |
| K- 07 30 25 05 | 32 | G 1 1/4 | 77,0      | 105,0     | 49          | 28          |
| K- 07 30 25 06 | 40 | G 1 1/2 | 87,0      | 120,0     | 56          | 32          |
| K- 07 30 25 07 | 50 | G 2     | 103,0     | 140,0     | 69          | 41          |