


# K-T-STUECKE IG 1 2

Tees, female-female-female

**HANSA FLEX**

## Vlastnosti

|                  |                              |
|------------------|------------------------------|
| Provozní tlak    | 60 bar                       |
| Provozní teplota | Max. 150 °C                  |
| Závit vnitřní    | Parallel to DIN EN ISO 228-1 |
| Materiál         | poniklovaná mosaz            |



## Upozornění

Další údaje na dotaz.

## Výrobek

| Označení       | Závit | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|-------|------------|------------|-------|
| K- 07 40 48 92 | M 5   | 22,0       | 11,0       | 9 mm  |
| K- 07 40 11 04 | G 1/8 | 42,0       | 21,0       | 10 mm |
| K- 07 40 11 05 | G 1/4 | 51,0       | 25,5       | 13 mm |
| K- 07 40 11 06 | G 3/8 | 56,0       | 28,0       | 17 mm |
| K- 07 40 11 07 | G 1/2 | 67,0       | 33,5       | 21 mm |
| K- 07 40 11 14 | G 3/4 | 73,0       | 36,5       | 25 mm |
| K- 07 40 11 15 | G 1   | 90,0       | 45,0       | 30 mm |