
## K-PROP REGELVE SENTRONIC D

Proportional control valves, digital, 24 VDC



Vlastnosti			
Teplota média	0 - 60 °C		
Teplota okolí	0 - 50 °C		
Média	Air or neutral gases (≤ 50 µm filter specified)		
Rozmezí tlaku	0 - 10 bar		
Ovládání	0 to 10 V (on request: 0 to 20 mA or 4 to 20 mA)		
Požadovaná hodnota elektrická	0 - 10 V		
Analogový výstup	0 - 10 V		
Ovládání	Proportional solenoid valve		
Digitální výstup	Pressure switch output PNP +/- 5%		
Poloha Failsafe	Pressure relieved in case of loss of voltage		
Vnitřní součásti	POM		
Těsnicí materiál	Nitrilkaučuk		
Pouzdro	Aluminium		





## Upozornění

Další údaje na dotaz.

## **Popis**

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital. <a href="https://document.org/repressure-negative-ne

Výrobek					
Označení	Přípoj	DN	Průtok	В	С
			(L/min)		(mm)
K- 07 25 10 04	G 1/8	4	780	52,0 mm	112,0
K- 07 25 10 05	G 1/4	4	780	52,0 mm	112,0
K- 07 25 10 06	G 1/4	8	1750	66,0 mm	138,0
K- 07 25 10 07	G 3/8	8	1750	66,0 mm	138,0