

# K-WTEH 2-TLG MET TROPF MULTIFIX MIN

Service units, 2-piece with metal bowl and metal sight dome

**HANSA FLEX**

## Vlastnosti

|                                |  |
|--------------------------------|--|
| Tlak na vstupu                 | Max. 12 bar (also for metal tank!)                             |
| Teplota média                  | max. 60 °C   |
| Teplota okolí                  | Max. 60 °C   |
| Šířka póru ve filtrační vložce | 5 µm   |
| Těsnicí materiál               | Nitrilkaučuk   |
| Kryt pružiny                   | POM-brass  |
| Pouzdro                        | Die-cast zinc  |
| Odkapávací nástavec            | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)           |
| Drain valve                    | Semi-automatic   |
| Měření hodnoty průtoku         | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



## Upozornění

Další údaje na dotaz.

## Popis

Two or three-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Upozornění k objednávkám

Lockable service units available on request. If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.

## Výrobek

| Označení       | Závít | Regulační rozsah | Průtok (L/min) | A (mm) | B        | C (mm) | D (mm) | DN | Konstrukční velikost |
|----------------|-------|------------------|----------------|--------|----------|--------|--------|----|----------------------|
| K- 07 25 01 26 | G 1/8 | 0.5 - 10 bar     | 700            | 80,0   | 162,0 mm | 63,0   | 99,0   | 5  | 0                    |
| K- 07 25 01 28 | G 1/4 | 0.5 - 10 bar     | 700            | 80,0   | 162,0 mm | 63,0   | 99,0   | 5  | 0                    |

## Náhradní díly

|                                |  |
|--------------------------------|--|
| K-HALTERBAUSATZ                | Holder                                       |
| K-AUTOMAT ABLASSVENTIL         | Automatic drain valve                        |
| K-SCHALTTAFELMUTTER            | Nut  |
| K-KOPPELPAKET MEHR             | Coupling packet                              |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter                    |
| K-ERSATZBEHAELTER MULTI MINI   | Spare tank »multifix-mini« & »standard-mini« |
| K-FILTERELEMENT                | Filter element                               |
| K-VERSCHLEI-SATZ               | Set of wearing parts                         |
| K-TROPFAUFSATZ POLYCARBO 1     | Drip attachment polycarbonate                |
| K-TROPFAUFSATZ METALL          | Drip attachment metal                        |