


K-KOLST LOSE ZYL

Rodless cylinders

HANSA FLEX

Vlastnosti

Média	Filtered (50 µm), unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Pracovní tlak	1 to 8 bar
Teplotní rozsah	-15 °C to +80 °C
Pouzdro	Jacket made from anodised aluminium alloy
vnitřní/vnější pás	Stainless steel
Saně (vedení pístu)	Anodised aluminium alloy
Těsnicí materiál	NBR for speeds up to 1 m/s



Popis

These double-acting cylinders can also be supplied with strokes greater than 5 m, providing the stroke length is approximately equal to the overall length. They are equipped with magnets as standard for indicating the position as well as pneumatic, adjustable end position cushioning. Limit switches and hydraulic shock absorbers can be mounted as add-on modules.

Upozornění k objednávkám

All strokes can also be supplied in 1 mm steps on request. Ø 16 to 5000 mm, Ø 25, 32, 40 to 5700 mm and Ø 63 to 5500 mm. Versions with an integrated linear guide can be supplied on request (up to 50 x lateral load).

Další informace

Important: The scope of supply does not include a connector. Please order separately.

Výrobek

Označení	Síla 6 bar (N)	Ø pístu	Zdvih (mm)	Přípoj	Max. boční zatížení
K- 07 15 07 34	110	16 mm	100	M 5	0.3 Nm
K- 07 15 07 35	110	16 mm	200	M 5	0.3 Nm
K- 07 15 07 36	110	16 mm	300	M 5	0.3 Nm
K- 07 15 07 37	110	16 mm	400	M 5	0.3 Nm
K- 07 15 07 38	110	16 mm	500	M 5	0.3 Nm
K- 07 15 07 39	110	16 mm	600	M 5	0.3 Nm
K- 07 15 07 40	110	16 mm	700	M 5	0.3 Nm
K- 07 15 07 41	110	16 mm	800	M 5	0.3 Nm
K- 07 15 07 42	110	16 mm	900	M 5	0.3 Nm
K- 07 15 07 43	110	16 mm	1000	M 5	0.3 Nm
K- 07 15 07 44	110	16 mm	1200	M 5	0.3 Nm
K- 07 15 07 45	110	16 mm	1400	M 5	0.3 Nm
K- 07 15 07 46	110	16 mm	2000	M 5	0.3 Nm
K- 07 15 07 47	250	25 mm	100	G 1/8	1.0 Nm
K- 07 15 07 48	250	25 mm	200	G 1/8	1.0 Nm
K- 07 15 07 49	250	25 mm	300	G 1/8	1.0 Nm
K- 07 15 07 50	250	25 mm	400	G 1/8	1.0 Nm
K- 07 15 07 51	250	25 mm	500	G 1/8	1.0 Nm
K- 07 15 07 52	250	25 mm	600	G 1/8	1.0 Nm
K- 07 15 07 53	250	25 mm	700	G 1/8	1.0 Nm
K- 07 15 07 54	250	25 mm	800	G 1/8	1.0 Nm
K- 07 15 07 55	250	25 mm	900	G 1/8	1.0 Nm
K- 07 15 07 56	250	25 mm	1000	G 1/8	1.0 Nm
K- 07 15 07 57	250	25 mm	1200	G 1/8	1.0 Nm
K- 07 15 07 58	250	25 mm	1400	G 1/8	1.0 Nm
K- 07 15 07 59	250	25 mm	2000	G 1/8	1.0 Nm
K- 07 15 07 60	420	32 mm	100	G 1/4	2.0 Nm
K- 07 15 07 61	420	32 mm	200	G 1/4	2.0 Nm
K- 07 15 07 62	420	32 mm	300	G 1/4	2.0 Nm
K- 07 15 07 63	420	32 mm	400	G 1/4	2.0 Nm
K- 07 15 07 64	420	32 mm	500	G 1/4	2.0 Nm
K- 07 15 07 65	420	32 mm	600	G 1/4	2.0 Nm
K- 07 15 07 66	420	32 mm	700	G 1/4	2.0 Nm
K- 07 15 07 67	420	32 mm	800	G 1/4	2.0 Nm
K- 07 15 07 68	420	32 mm	900	G 1/4	2.0 Nm



Navzdory nejpečlivější kontrole nemůžeme vyloučit chyby a nepřijímáme žádnou záruku za obsažené údaje.

18.04.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-KOLST LOSE ZYL

Rodless cylinders

HANSA FLEX

Výrobek

Označení	Síla 6 bar (N)	Ø pístu	Zdvih (mm)	Přípoj	Max. boční zatížení
K- 07 15 07 69	420	32 mm	1000	G 1/4	2.0 Nm
K- 07 15 07 70	420	32 mm	1200	G 1/4	2.0 Nm
K- 07 15 07 71	420	32 mm	1400	G 1/4	2.0 Nm
K- 07 15 07 72	420	32 mm	2000	G 1/4	2.0 Nm
K- 07 15 07 73	640	40 mm	100	G 1/4	4.0 Nm
K- 07 15 07 74	640	40 mm	200	G 1/4	4.0 Nm
K- 07 15 07 75	640	40 mm	300	G 1/4	4.0 Nm
K- 07 15 07 76	640	40 mm	400	G 1/4	4.0 Nm
K- 07 15 07 77	640	40 mm	500	G 1/4	4.0 Nm
K- 07 15 07 78	640	40 mm	600	G 1/4	4.0 Nm
K- 07 15 07 79	640	40 mm	700	G 1/4	4.0 Nm
K- 07 15 07 80	640	40 mm	800	G 1/4	4.0 Nm
K- 07 15 07 81	640	40 mm	900	G 1/4	4.0 Nm
K- 07 15 07 82	640	40 mm	1000	G 1/4	4.0 Nm
K- 07 15 07 83	640	40 mm	1200	G 1/4	4.0 Nm
K- 07 15 07 84	640	40 mm	1400	G 1/4	4.0 Nm
K- 07 15 07 85	640	40 mm	2000	G 1/4	4.0 Nm
K- 07 15 07 86	1550	63 mm	100	G 3/8	8.0 Nm
K- 07 15 07 87	1550	63 mm	200	G 3/8	8.0 Nm
K- 07 15 07 88	1550	63 mm	300	G 3/8	8.0 Nm
K- 07 15 07 89	1550	63 mm	400	G 3/8	8.0 Nm
K- 07 15 07 90	1550	63 mm	500	G 3/8	8.0 Nm
K- 07 15 07 91	1550	63 mm	600	G 3/8	8.0 Nm
K- 07 15 07 92	1550	63 mm	700	G 3/8	8.0 Nm
K- 07 15 07 93	1550	63 mm	800	G 3/8	8.0 Nm
K- 07 15 07 94	1550	63 mm	900	G 3/8	8.0 Nm
K- 07 15 07 95	1550	63 mm	1000	G 3/8	8.0 Nm
K- 07 15 07 96	1550	63 mm	1200	G 3/8	8.0 Nm
K- 07 15 07 97	1550	63 mm	1400	G 3/8	8.0 Nm
K- 07 15 07 98	1550	63 mm	2000	G 3/8	8.0 Nm

Příslušenství

K-FUSSBEFESTIGUNG 4	Foot model
K-ZST	Intermediate foot
K-SENSOREN T-NUT 1	Sensor for T-slot
K-ABDECKBAENDER	Bar for grooving (500 mm)