
K-STOPPVENTILE STECK

Stop valves, ports 2 and 3 with plug connection



Vlastnosti					
Pracovní tlak	Max. 10 bar				
Ovládací tlak	1 - 5 bar, depending on operating pressure				
Teplota média	max. 70 °C				
Vestavná poloha	Any. Ring pieces can still be rotated 360° after the valve has been tightened				
Těsnicí materiál	Perbunan				





Upozornění

Další údaje na dotaz.

Popis

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Výrobek							
Označení	Port 1	Port 2	přípoj 3	Materiál	B (mm)	C (mm)	
K- 07 15 20 50	G 1/8	6 mm	4 mm	Nickel-plated brass	52,0	25,0	
K- 07 15 20 49	G 1/4	6 mm	4 mm	Nickel-plated brass	58,0	28,0	
K- 07 15 20 51	G 3/8	8 mm	4 mm	Nickel-plated brass	63,0	32,0	
K- 07 15 20 48	G 1/2	12 mm	4 mm	Nickel-plated brass	72,0	41,0	