

K-SPIR SCHL KUPPL SET SVKM

Spiral hose and coupling kits, with quick disconnect couplings DN 7.6

HANSA FLEX

Vlastnosti

| | |
|---------------|------------------|
| Provozní tlak | 10 bar |
| Teplota média | -20 °C to +60 °C |



Upozornění

Další údaje na dotaz.

Popis

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

Výrobek

| Označení | Rozměr hadice | Ø spirály (mm) | Pracovní délka (m) |
|----------------|----------------|-------------------|-----------------------|
| K- 07 10 07 59 | 10 mm x 6,5 mm | 52 | 4,0 |
| K- 07 10 07 60 | 10 mm x 6,5 mm | 52 | 6,0 |
| K- 07 10 07 61 | 10 mm x 6,5 mm | 52 | 8,0 |
| K- 07 10 07 62 | 12 mm x 8 mm | 65 | 4,0 |
| K- 07 10 07 63 | 12 mm x 8 mm | 65 | 6,0 |
| K- 07 10 07 64 | 12 mm x 8 mm | 65 | 8,0 |