
K-VENTILSCHEIBE HDM 6

Valve discs for HDM valve terminal with 6 mm port

Vlastnosti

Média	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Pracovní tlak	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Ovládací tlak	3 - 7 bar
Teplotní rozsah	-10 °C to +60 °C
Průtok	200 Nl/min (Ø 4), 500 Nl/min (Ø 6), 800 Nl/min (Ø 8)
Počet ovládání	Max. 16 (e.g. 16 spring return valves)
Pomocné ruční ovládání	Latching (bistable), Monostable (non-latching) version also available on request
Příkon	0.6 W per pilot
Stupeň krytí	IP 65



Upozornění

Další údaje na dotaz.

Popis

These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates.Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Další informace

Important: The scope of supply does not include a connector. Please order separately.

Výrobek

Označení	Funkce
K- 07 15 20 60	2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted
K- 07 15 20 67	2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised
K- 07 15 20 62	3/2-way, NC, monostable and 3/2-way, NO, monostable
K- 07 15 20 66	5/2-way, monostable
K- 07 15 20 59	5/2-way, monostable (uses only one pin, two signals assigned)
K- 07 15 20 61	5/2-way, bistable (pulse valve)
K- 07 15 20 64	5/3-way, mid-position closed

Navzdory nejpečlivější kontrole nemůžeme vyloučit chyby a nepřejímáme žádnou záruku za obsažené údaje.