

# K-FLACHDUESE LAERMARME

Low-noise flat nozzles

**HANSA FLEX**



## Upozornění

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

## Popis

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

## Výrobek

| Označení       | Šířka trysky<br>(mm) | Závit      | Délka<br>(mm) | Materiál            | Diagram |
|----------------|----------------------|------------|---------------|---------------------|---------|
| K- 07 10 09 60 | 21,5                 | G 1/4 male | 100,0         | Nickel-plated brass | 11      |
| K- 07 10 09 61 | 29,0                 | G 3/8 male | 100,0         | Nickel-plated brass | 12      |
| K- 07 10 09 62 | 16,5                 | G 3/8 male | 50,0          | Galvanised steel    | 14      |
| K- 07 10 09 63 | 21,0                 | G 1/4 male | 100,0         | Nickel-plated brass | 13      |
| K- 07 10 09 64 | 29,0                 | G 3/8 male | 100,0         | Nickel-plated brass | 15      |