


K-KURZH ZYL DOPPELW IG ASQ

Short-stroke cylinders, double-acting, with magnet, non-cushioned, with female thread, »ACQ« Series

HANSA FLEX

Vlastnosti

Média	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Pracovní tlak	1 - 10 bar (double-acting); 2 - 10 bar (single-acting)
Teplotní rozsah	-20 °C to +80 °C
Pístnice	Hardened steel, thick-chromed
Píst	Brass (12 to 16 mm); Aluminium (20 to 100 mm)
Těsnicí materiál	Nitrilkaučuk
Trubka válce	Aluminium



Upozornění

Další údaje na dotaz.

Popis

Specially for use where space is in short supply. Version with magnetic piston. Short-stroke cylinder in two different versions: Series "ACQ", double-acting, Ø 12 – 100

Další informace

Important: The scope of supply does not include a connector. Please order separately.

Other piston-Ø and stroke versions available on request.

Výrobek

Označení	Ø pístu	Zdvih (mm)	Provedení	Ø pístnice (mm)	Závit vnitřní pístnice
K- 07 15 12 15	12 mm	5	1	6	M 3 x 0.5
K- 07 15 12 16	12 mm	10	1	6	M 3 x 0.5
K- 07 15 12 17	12 mm	20	1	6	M 3 x 0.5
K- 07 15 12 18	12 mm	25	1	6	M 3 x 0.5
K- 07 15 12 19	12 mm	30	1	6	M 3 x 0.5
K- 07 15 12 20	12 mm	35	1	6	M 3 x 0.5
K- 07 15 12 21	12 mm	40	1	6	M 3 x 0.5
K- 07 15 12 22	12 mm	45	1	6	M 3 x 0.5
K- 07 15 12 23	12 mm	50	1	6	M 3 x 0.5
K- 07 15 12 24	16 mm	5	1	8	M 4 x 0.7
K- 07 15 12 25	16 mm	10	1	8	M 4 x 0.7
K- 07 15 12 26	16 mm	20	1	8	M 4 x 0.7
K- 07 15 12 27	16 mm	25	1	8	M 4 x 0.7
K- 07 15 12 28	16 mm	30	1	8	M 4 x 0.7
K- 07 15 12 29	16 mm	35	1	8	M 4 x 0.7
K- 07 15 12 30	16 mm	40	1	8	M 4 x 0.7
K- 07 15 12 31	16 mm	45	1	8	M 4 x 0.7
K- 07 15 12 32	16 mm	50	1	8	M 4 x 0.7
K- 07 15 12 33	16 mm	55	1	8	M 4 x 0.7
K- 07 15 12 34	16 mm	60	1	8	M 4 x 0.7
K- 07 15 12 35	20 mm	5	2	10	M 5 x 0.8
K- 07 15 12 36	20 mm	10	2	10	M 5 x 0.8
K- 07 15 12 37	20 mm	20	2	10	M 5 x 0.8
K- 07 15 12 38	20 mm	25	2	10	M 5 x 0.8
K- 07 15 12 39	20 mm	30	2	10	M 5 x 0.8
K- 07 15 12 40	20 mm	35	2	10	M 5 x 0.8
K- 07 15 12 41	20 mm	40	2	10	M 5 x 0.8
K- 07 15 12 42	20 mm	45	2	10	M 5 x 0.8
K- 07 15 12 43	20 mm	50	2	10	M 5 x 0.8
K- 07 15 12 44	20 mm	55	2	10	M 5 x 0.8
K- 07 15 12 45	20 mm	60	2	10	M 5 x 0.8
K- 07 15 12 46	20 mm	70	2	10	M 5 x 0.8
K- 07 15 12 47	20 mm	75	2	10	M 5 x 0.8
K- 07 15 12 48	20 mm	80	2	10	M 5 x 0.8
K- 07 15 12 49	25 mm	5	2	12	M 6 x 1



Navzdory nejpečlivější kontrole nemůžeme vyloučit chyby a nepřejímáme žádnou záruku za obsažené údaje.

06.06.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-KURZH ZYL DOPPELW IG ASQ

Short-stroke cylinders, double-acting, with magnet, non-cushioned, with female thread, »ACQ« Series

HANSA FLEX

Výrobek

Označení	Ø pístu	Zdvih (mm)	Provedení	Ø pístnice (mm)	Závit vnitřní pístnice
K-07 15 12 50	25 mm	10	2	12	M 6 x 1
K-07 15 12 51	25 mm	20	2	12	M 6 x 1
K-07 15 12 52	25 mm	25	2	12	M 6 x 1
K-07 15 12 53	25 mm	30	2	12	M 6 x 1
K-07 15 12 54	25 mm	35	2	12	M 6 x 1
K-07 15 12 55	25 mm	40	2	12	M 6 x 1
K-07 15 12 56	25 mm	45	2	12	M 6 x 1
K-07 15 12 57	25 mm	50	2	12	M 6 x 1
K-07 15 12 58	25 mm	55	2	12	M 6 x 1
K-07 15 12 59	25 mm	60	2	12	M 6 x 1
K-07 15 12 60	25 mm	70	2	12	M 6 x 1
K-07 15 12 61	25 mm	75	2	12	M 6 x 1
K-07 15 12 62	25 mm	80	2	12	M 6 x 1
K-07 15 12 63	32 mm	5	3	16	M 8 x 1.25
K-07 15 12 64	32 mm	10	3	16	M 8 x 1.25
K-07 15 12 65	32 mm	20	3	16	M 8 x 1.25
K-07 15 12 66	32 mm	25	3	16	M 8 x 1.25
K-07 15 12 67	32 mm	30	3	16	M 8 x 1.25
K-07 15 12 68	32 mm	35	3	16	M 8 x 1.25
K-07 15 12 69	32 mm	40	3	16	M 8 x 1.25
K-07 15 12 70	32 mm	45	3	16	M 8 x 1.25
K-07 15 12 71	32 mm	50	3	16	M 8 x 1.25
K-07 15 12 72	32 mm	55	3	16	M 8 x 1.25
K-07 15 12 73	32 mm	60	3	16	M 8 x 1.25
K-07 15 12 74	32 mm	70	3	16	M 8 x 1.25
K-07 15 12 75	32 mm	75	3	16	M 8 x 1.25
K-07 15 12 76	32 mm	80	3	16	M 8 x 1.25
K-07 15 12 77	40 mm	5	3	16	M 8 x 1.25
K-07 15 12 78	40 mm	10	3	16	M 8 x 1.25
K-07 15 12 79	40 mm	20	3	16	M 8 x 1.25
K-07 15 12 80	40 mm	25	3	16	M 8 x 1.25
K-07 15 12 81	40 mm	30	3	16	M 8 x 1.25
K-07 15 12 82	40 mm	35	3	16	M 8 x 1.25
K-07 15 12 83	40 mm	40	3	16	M 8 x 1.25
K-07 15 12 84	40 mm	45	3	16	M 8 x 1.25
K-07 15 12 85	40 mm	50	3	16	M 8 x 1.25
K-07 15 12 86	40 mm	55	3	16	M 8 x 1.25
K-07 15 12 87	40 mm	60	3	16	M 8 x 1.25
K-07 15 12 88	40 mm	70	3	16	M 8 x 1.25
K-07 15 12 89	40 mm	75	3	16	M 8 x 1.25
K-07 15 12 90	40 mm	80	3	16	M 8 x 1.25
K-07 15 12 91	50 mm	5	3	20	M 10 x 1.5
K-07 15 12 92	50 mm	10	3	20	M 10 x 1.5
K-07 15 12 93	50 mm	20	3	20	M 10 x 1.5
K-07 15 12 94	50 mm	25	3	20	M 10 x 1.5
K-07 15 12 95	50 mm	30	3	20	M 10 x 1.5
K-07 15 12 96	50 mm	35	3	20	M 10 x 1.5
K-07 15 12 97	50 mm	40	3	20	M 10 x 1.5
K-07 15 12 98	50 mm	45	3	20	M 10 x 1.5
K-07 15 12 99	50 mm	50	3	20	M 10 x 1.5
K-07 15 13 00	50 mm	55	3	20	M 10 x 1.5
K-07 15 13 01	50 mm	60	3	20	M 10 x 1.5
K-07 15 13 02	50 mm	70	3	20	M 10 x 1.5
K-07 15 13 03	50 mm	75	3	20	M 10 x 1.5
K-07 15 13 04	50 mm	80	3	20	M 10 x 1.5
K-07 15 13 05	63 mm	5	3	20	M 10 x 1.5
K-07 15 13 06	63 mm	10	3	20	M 10 x 1.5
K-07 15 13 07	63 mm	20	3	20	M 10 x 1.5
K-07 15 13 08	63 mm	25	3	20	M 10 x 1.5
K-07 15 13 09	63 mm	30	3	20	M 10 x 1.5
K-07 15 13 10	63 mm	35	3	20	M 10 x 1.5
K-07 15 13 11	63 mm	40	3	20	M 10 x 1.5



K-KURZH ZYL DOPPELW IG ASQ

Short-stroke cylinders, double-acting, with magnet, non-cushioned, with female thread, »ACQ« Series

HANSA FLEX

Výrobek

Označení	Ø pístu	Zdvih (mm)	Provedení	Ø pístnice (mm)	Závit vnitřní pístnice
K- 07 15 13 12	63 mm	45	3	20	M 10 x 1.5
K- 07 15 13 13	63 mm	50	3	20	M 10 x 1.5
K- 07 15 13 14	63 mm	55	3	20	M 10 x 1.5
K- 07 15 13 15	63 mm	60	3	20	M 10 x 1.5
K- 07 15 13 16	63 mm	70	3	20	M 10 x 1.5
K- 07 15 13 17	63 mm	75	3	20	M 10 x 1.5
K- 07 15 13 18	63 mm	80	3	20	M 10 x 1.5
K- 07 15 13 19	80 mm	5	3	25	M 16 x 2
K- 07 15 13 20	80 mm	10	3	25	M 16 x 2
K- 07 15 13 21	80 mm	20	3	25	M 16 x 2
K- 07 15 13 22	80 mm	25	3	25	M 16 x 2
K- 07 15 13 23	80 mm	30	3	25	M 16 x 2
K- 07 15 13 24	80 mm	35	3	25	M 16 x 2
K- 07 15 13 25	80 mm	40	3	25	M 16 x 2
K- 07 15 13 26	80 mm	45	3	25	M 16 x 2
K- 07 15 13 27	80 mm	50	3	25	M 16 x 2
K- 07 15 13 28	80 mm	55	3	25	M 16 x 2
K- 07 15 13 29	80 mm	60	3	25	M 16 x 2
K- 07 15 13 30	80 mm	70	3	25	M 16 x 2
K- 07 15 13 31	80 mm	75	3	25	M 16 x 2
K- 07 15 13 32	80 mm	80	3	25	M 16 x 2
K- 07 15 12 01	100 mm	5	3	32	M 20 x 2.5
K- 07 15 12 02	100 mm	10	3	32	M 20 x 2.5
K- 07 15 12 03	100 mm	20	3	32	M 20 x 2.5
K- 07 15 12 04	100 mm	25	3	32	M 20 x 2.5
K- 07 15 12 05	100 mm	30	3	32	M 20 x 2.5
K- 07 15 12 06	100 mm	35	3	32	M 20 x 2.5
K- 07 15 12 07	100 mm	40	3	32	M 20 x 2.5
K- 07 15 12 08	100 mm	45	3	32	M 20 x 2.5
K- 07 15 12 09	100 mm	50	3	32	M 20 x 2.5
K- 07 15 12 10	100 mm	55	3	32	M 20 x 2.5
K- 07 15 12 11	100 mm	60	3	32	M 20 x 2.5
K- 07 15 12 12	100 mm	70	3	32	M 20 x 2.5
K- 07 15 12 13	100 mm	75	3	32	M 20 x 2.5
K- 07 15 12 14	100 mm	80	3	32	M 20 x 2.5

Příslušenství

K-FUSSBEFESTIGUNG TYP LB 3	Foot model, »LB« type
K-FLANSCHBEFESTIGUNG TYP FA2	Flange model, »FA« type
K-SCHWENKGABELBEFESTIG CB 1	Female hinge model, »CB« type
K-GABELKOEPE TYP Y SET 1	Fork model, »Y« type (incl. threaded adapter)
K-GELENKAUGEN TYP UNIT SET 1	Rod eye model, »UNIT« type (incl. threaded adapter)
K-SENSOREN CS1 KH MIT STECKER	Sensors »CS1« type, cable with M8 plug
K-SENSOREN CS1 KH OHNE STECKER	Sensors »CS1« type, cable without plug