


# K-LKM S NW7,4 SCHL TUE

Safety couplings DN 7.4, with hose stem

**HANSA FLEX**

## Vlastnosti

|  |  |
|--|--|
| Provozní tlak  | Max. 12 bar, maximum static working pressure (non-pulsating) |
| Provozní tlak nasazovací průchodky a vsuvky          | 0 to 35 bar  |
| Průtok vzduchu                                       | 1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)              |
| Teplota média  | -20 °C to +60 °C   |
| Pouzdro, tělo ventilu                                | Nickel-plated brass  |
| Ventil   | Brass  |
| Odblokovací objímka                                  | Plastic  |
| Pružina, rozpěrný pojistný kroužek, kuličky, kuličky | Stainless steel  |
| Těsnicí materiál                                     | Nitrilkaučuk   |



## Upozornění

Další údaje na dotaz.

## Popis

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

## Výrobek

| Označení       | Přípoj        | Délka (mm) | SW (mm) |
|----------------|---------------|------------|---------|
| K- 07 35 03 04 | Stem, I.D. 6  | 71,2       | 22      |
| K- 07 35 03 05 | Stem, I.D. 8  | 71,2       | 22      |
| K- 07 35 03 06 | Stem, I.D. 9  | 71,2       | 22      |
| K- 07 35 03 07 | Stem, I.D. 10 | 71,2       | 22      |
| K- 07 35 03 08 | Stem, I.D. 13 | 71,2       | 22      |

## Přídavné elementy

|                            |   |
|----------------------------|---|
| K-NIPPEL KUPPL NW7 AG VZ   | Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male   |
| K-NIPPEL KUPPL NW7 IG VZ 2 | Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female |
| K-TUE 7,2 7,8 ST VZ 1      | Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,        |