

# K-SVKM NW 7,8 AG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, male

**HANSA FLEX**

## Vlastnosti

Provozní tlak	0 - 35 bar
Průtok vzduchu	2.100 l/min (at $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +40 °C
Závitový kus	Nickel-plated brass
Tělo ventilu	Steel, QPQ treated
Odblokovací objímka	Extremely robust, ergonomic plastic
Ventil, sídlo	Brass
Média	Only for clean compressed air
Těsnění	NBR
Pružina, rozpěrný pojistný kroužek, kuličky	stain less steel



## Upozornění

Další údaje na dotaz.

## Popis

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

## Výrobek

Označení	Přípoj	Délka (mm)	SW (mm)
K- 07 35 08 47	G 1/4 male	65,0	19
K- 07 35 08 48	G 3/8 male	65,0	19
K- 07 35 08 49	G 1/2 male	59,0	22

## Přídavné elementy

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass