

K-LKM S NW7,8 IG

Safety couplings DN 7.8, female

Vlastnosti

Provozní tlak	max. 20 bar
Průtok vzduchu	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +100 °C
Přípoj těla ventilu	Nickel-plated brass
Pružina, kuličky	Stainless-steel
Posuvná objímka	Anodised aluminium
Odblokovací objímka	Hardened and nickel-plated steel
Těsnicí materiál	Nitrilkaučuk



Upozornění

Další údaje na dotaz.

Popis

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Výrobek

Označení	Přípoj	Délka (mm)	SW (mm)
K- 07 35 08 85	G 1/4 female	75,0	19
K- 07 35 08 86	G 3/8 female	75,0	19
K- 07 35 08 87	G 1/2 female	80,0	24

Přídavné elementy

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass