


# K-SVKM NW 7,2 SCHL-ANSCHL MS

Quick disconnect couplings DN 7.2, nickel-plated brass, with hose connector, with swivel nut

**HANSA FLEX**

## Vlastnosti

Provozní tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Průtok vzduchu	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +100 °C
Pouzdro, objímka	Nickel-plated brass
Ventil	Brass with a bare metal surface
Pružina, rozpěrný pojistný kroužek	Stainless steel 1.4310
Blokovací kolíky	Stainless steel 1.4034
Těsnicí materiál	Nitrilkaučuk



## Upozornění

Další údaje na dotaz.

## Popis

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

## Výrobek

Označení	Přípoj	Délka (mm)	SW (mm)
K- 07 35 12 67	Hose connection 6 x 4	58,0	21
K- 07 35 07 24	Hose connection 8 x 6	45,0	21
K- 07 35 07 25	Hose connection 10 x 8	49,0	21
K- 07 35 07 26	Hose connection 12 x 9	49,0	21

## Přídavné elementy

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass