


K-ZFL VENTILINSEL HDM

Intermediate plates for HDM valve terminal

Vlastnosti

| | |
|-------------------------------|---|
| Média | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Pracovní tlak | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| Ovládací tlak | 3 - 7 bar |
| Teplotní rozsah | -10 °C to +60 °C |
| Průtok | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8) |
| Počet ovládaní | Max. 16 (e.g. 16 spring return valves) |
| Pomocné ruční ovládaní | Latching (bistable), Monostable (non-latching) version also available on request |
| Příkon | 0.6 W per pilot |
| Stupeň krytí | IP 65 |



Upozornění

Další údaje na dotaz.

Popis

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Další informace

Important: The scope of supply does not include a connector. Please order separately.

Výrobek

| Označení | Funkce |
|----------------|--|
| K- 07 15 22 51 | With additional pilots and exhausts |
| K- 07 15 22 52 | With separate pilots (for multi-pressure systems) |
| K- 07 15 22 44 | With separate exhausts (for multi-pressure system) |