


# K-RD DURCHGANGSFORM LEI VA

Check valve - straight-way type, lightweight series, stainless steel

**HANSA FLEX**

## Vlastnosti

|                  |                        |
|------------------|------------------------|
| Provozní tlak    | 2 - 16 bar             |
| Provozní teplota | -20 °C to +150 °C      |
| Otevírací tlak   | min. 0.03 bar          |
| Těsnicí materiál | FKM                    |
| Pružina          | Stainless steel 1.4301 |
| Pouzdro          | Stainless steel 1.4301 |



## Upozornění

Další údaje na dotaz.

## Popis

Stainless steel check valve with full bore and very low opening pressure, no maintenance required. Applications: Compressed air, water, neutral gases, gaseous and liquid non-corrosive media, oils.

## Výrobek

| Označení       | Závit   | A<br>(mm) | C<br>(mm) | L<br>(mm) |
|----------------|---------|-----------|-----------|-----------|
| K- 07 30 29 23 | G 1/4   | 20,0      | 32,0      | 55,9      |
| K- 07 30 29 28 | G 3/8   | 20,0      | 32,0      | 56,0      |
| K- 07 30 29 22 | G 1/2   | 25,0      | 32,0      | 55,6      |
| K- 07 30 29 27 | G 3/4   | 29,0      | 44,0      | 66,7      |
| K- 07 30 29 19 | G 1     | 36,0      | 53,0      | 83,6      |
| K- 07 30 29 21 | G 1 1/4 | 45,0      | 62,0      | 96,0      |
| K- 07 30 29 20 | G 1 1/2 | 51,0      | 78,0      | 114,0     |
| K- 07 30 29 24 | G 2     | 64,0      | 89,0      | 120,5     |
| K- 07 30 29 25 | G 2 1/2 | 80,0      | 113,0     | 141,5     |
| K- 07 30 29 26 | G 3     | 94,0      | 132,0     | 160,0     |