

K-WV 3/2 5/2 NAMUR LB FR

3/2- and 5/2-way spool valves with NAMUR style interface and combined spring return

HANSA FLEX

Vlastnosti

Média	Air, neutral gases (filtered)
Pracovní tlak	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
Provozní teplota	-20 °C to +50 °C
Přípoj 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Přípoj 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Elektrické zapojení	Plug connector PG 9
Balení obsahuje	Plug connector PG 9, conversion plate, screws and seal
Příkon	3 W=/5 VA~
Pouzdro	Anodised aluminium
Šoupátko	Stainless steel
Těsnicí materiál	Nitrilkaučuk



Upozornění

Další údaje na dotaz.

Popis

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Výrobek

Označení	Napětí	Port 1	Přípoj 3 + 5	DN	Průtok (L/min)
K- 07 15 00 15	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 16	24 V DC	G 1/4	G 1/4	7	1250