

K-VSTO POM

Plugs

HANSA FLEX

Vlastnosti

Pracovní tlak	0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)
Provozní teplota	-20 °C to +70 °C in air; +1 °C to +70 °C in water
Materiál	Acetalpolymerisat (POM)
Těsnicí materiál	Nitrilkaučuk



Upozornění

Další údaje na dotaz.

Popis

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Výrobek

Označení	Barva	L1 (mm)	Hrdlo trubky (mm)
K- 07 40 29 11	červená	28,0	4
K- 07 40 29 12	červená	28,0	5
K- 07 40 29 13	červená	30,0	6
K- 07 40 29 14	červená	31,0	8
K- 07 40 29 15	červená	36,5	10
K- 07 40 29 16	červená	38,5	12
K- 07 40 29 17	černá	45,0	15
K- 07 40 29 18	černá	41,5	18
K- 07 40 29 19	černá	45,0	22
K- 07 40 29 20	černá	56,0	28