

# K-GMM 2

Glycerine-filled pressure gauges, CrNi steel type

**HANSA FLEX**

## Vlastnosti

|                 |   |
|-----------------|---|
| Typ             | 233.30  |
| Provedení       | Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)     |
| Použití         | For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere |
| Jakostní třída  | 1,6 (Ø 63 mm), 1,0 (Ø 100 mm)   |
| Teplota média   | max. +100 °C  |
| Teplota okolí   | -20 °C až +60 °C  |
| Pouzdro         | CrNi steel  |
| Průhledové sklo | Laminated safety glass Ø 63 = Polycarbonate   |



## Upozornění

Další údaje na dotaz.

## Výrobek

| Označení       | Rozsah měřená | Ø (mm) | Přípoj |
|----------------|---------------|--------|--------|
| K- 07 20 07 03 | -1 / 0.0 bar  | 63,0   | G 1/4" |
| K- 07 20 07 04 | 0 - 4.0 bar   | 63,0   | G 1/4" |
| K- 07 20 07 05 | 0 - 6.0 bar   | 63,0   | G 1/4" |
| K- 07 20 07 06 | 0 - 10.0 bar  | 63,0   | G 1/4" |
| K- 07 20 07 07 | 0 - 16.0 bar  | 63,0   | G 1/4" |
| K- 07 20 07 08 | 0 - 25.0 bar  | 63,0   | G 1/4" |
| K- 07 20 07 09 | 0 - 40.0 bar  | 63,0   | G 1/4" |
| K- 07 20 07 10 | 0 - 60.0 bar  | 63,0   | G 1/4" |
| K- 07 20 07 11 | 0 - 100.0 bar | 63,0   | G 1/4" |
| K- 07 20 07 12 | 0 - 160.0 bar | 63,0   | G 1/4" |
| K- 07 20 07 13 | 0 - 250.0 bar | 63,0   | G 1/4" |
| K- 07 20 07 14 | 0 - 400.0 bar | 63,0   | G 1/4" |
| K- 07 20 01 79 | -1 / 0.0 bar  | 100,0  | G 1/2" |
| K- 07 20 01 80 | -1 / +1.5 bar | 100,0  | G 1/2" |
| K- 07 20 01 81 | -1 / +3.0 bar | 100,0  | G 1/2" |
| K- 07 20 01 82 | -1 / +5.0 bar | 100,0  | G 1/2" |
| K- 07 20 01 83 | -1 / +9.0 bar | 100,0  | G 1/2" |
| K- 07 20 01 84 | 0 - 2.5 bar   | 100,0  | G 1/2" |
| K- 07 20 01 85 | 0 - 4.0 bar   | 100,0  | G 1/2" |
| K- 07 20 01 86 | 0 - 6.0 bar   | 100,0  | G 1/2" |
| K- 07 20 01 87 | 0 - 10.0 bar  | 100,0  | G 1/2" |
| K- 07 20 01 88 | 0 - 16.0 bar  | 100,0  | G 1/2" |
| K- 07 20 01 89 | 0 - 25.0 bar  | 100,0  | G 1/2" |
| K- 07 20 01 90 | 0 - 40.0 bar  | 100,0  | G 1/2" |
| K- 07 20 01 91 | 0 - 60.0 bar  | 100,0  | G 1/2" |
| K- 07 20 01 92 | 0 - 100.0 bar | 100,0  | G 1/2" |
| K- 07 20 01 93 | 0 - 160.0 bar | 100,0  | G 1/2" |
| K- 07 20 01 94 | 0 - 250.0 bar | 100,0  | G 1/2" |
| K- 07 20 01 95 | 0 - 400.0 bar | 100,0  | G 1/2" |
| K- 07 20 01 96 | 0 - 600.0 bar | 100,0  | G 1/2" |