

# K-LKM S NW7,4 DREH SCHL TUE VA

Safety couplings DN 7.4, stainless steel 1.4404, with hose stem, swivel type

**HANSA FLEX**

## Vlastnosti

Provozní tlak	max. 10 bar
Průtok vzduchu	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Teplota média	-20 °C to +150 °C
Pouzdro	Stainless steel 1.4404
Závit	Stainless steel 1.4404
Vnitřní součásti	Stainless steel 1.4404
Hlava, ventil	Stainless steel 1.4404
Těsnicí materiál	FKM



## Upozornění

Not suitable for hitting / pulsating tools.

Další údaje na dotaz.

## Popis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## Další informace

Not suitable for hitting / pulsating tools.

## Výrobek

Označení	Přípoj	Délka (mm)	SW (mm)
K- 07 35 12 83	Stem, I.D. 6	88,5	21
K- 07 35 12 85	Stem, I.D. 9	88,5	21
K- 07 35 12 86	Stem, I.D. 13	88,5	21