

# K-L-STECK VB

Union elbows

**HANSA FLEX**

## Vlastnosti

|                   |                     |
|-------------------|---------------------|
| Pracovní tlak     | Max. 16 bar         |
| Provozní teplota  | -20 °C to +150 °C   |
| Materiál          | poniklovaná mosaz   |
| Přítlačný kroužek | Nickel-plated brass |
| Rozpínací kroužek | Stainless steel     |



## Upozornění

Další údaje na dotaz.

## Popis

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Výrobek

| Označení       | pro vnější Ø hadice | L1<br>(mm) | L2<br>(mm) |
|----------------|---------------------|------------|------------|
| K- 07 40 27 53 | 4 mm                | 17,5       | 17,5       |
| K- 07 40 27 54 | 6 mm                | 20,0       | 20,0       |
| K- 07 40 27 55 | 8 mm                | 23,0       | 23,0       |
| K- 07 40 27 56 | 10 mm               | 25,0       | 25,0       |
| K- 07 40 47 79 | 12 mm               | 27,5       | 27,5       |
| K- 07 40 47 80 | 14 mm               | 31,0       | 31,0       |