K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

Vlastnosti

Použití	Air, gases, oils, greases, fuels, organic and inorganic substances
Provozní teplota	-40 °C to +100 °C
Typ připojení	connection nipples and coupling NW 7,2



Upozornění

Další údaje na dotaz.

Popis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Výrobek

Označení	Ø hadice vnitřní (mm)	Ø hadice vnější (mm)	Ø spirály vnější (mm)	Vinutí	Max. working pressure resistance at 23°C (bar)	Max. pracovní délka (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Příslušenství

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Navzdory nejpečlivější kontrole nemůžeme vyloučit chyby a nepřejímáme žádnou záruku za obsažené údaje.