

K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

HANSA FLEX

Vlastnosti

| | |
|------------------|--|
| Použití | Air, gases, oils, greases, fuels, organic and inorganic substances |
| Provozní teplota | -40 °C to +100 °C |
| Typ připojení | connection nipples and coupling NW 7,2 |



Upozornění

Další údaje na dotaz.

Popis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Výrobek

| Označení | Ø hadice vnitřní (mm) | Ø hadice vnější (mm) | Ø spirály vnější (mm) | Vinutí | Max. working pressure resistance at 23°C (bar) | Max. pracovní délka (m) |
|----------------|-----------------------|----------------------|-----------------------|--------|--|-------------------------|
| K- 07 10 12 95 | 6,3 | 7,9 | 75 | 15 | 13 | 2,5 |
| K- 07 10 12 96 | 6,3 | 7,9 | 75 | 30 | 13 | 5,0 |
| K- 07 10 12 97 | 6,3 | 7,9 | 75 | 45 | 13 | 7,5 |
| K- 07 10 12 65 | 7,9 | 9,5 | 115 | 10 | 12 | 2,5 |
| K- 07 10 12 66 | 7,9 | 9,5 | 115 | 20 | 12 | 5,0 |
| K- 07 10 12 67 | 7,9 | 9,5 | 115 | 30 | 12 | 7,5 |
| K- 07 10 12 68 | 9,5 | 11,8 | 140 | 8 | 11 | 2,5 |
| K- 07 10 12 69 | 9,5 | 11,8 | 140 | 15 | 11 | 5,0 |
| K- 07 10 12 70 | 9,5 | 11,8 | 140 | 23 | 11 | 7,5 |

Příslušenství

| | |
|--------------------------|-------------------------------------|
| K-DREHBARE VERSCHR KNICK | Swivel adapters with kink protector |
| K-STARRE VERSCHRAUBUNG | Rigid adapters with kink protector |