

K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA FLEX

Vlastnosti

| | |
|--------------------|--|
| Max. provozní tlak | 0,7 MPa |
| Min. provozní tlak | 0.10 MPa |
| Provedení | rack and pinion |
| Teplota média | 0 °C to +60 °C |
| Teplota okolí | 0 °C to +60 °C |
| Úhel natočení | 0 to 190° |
| Média | Stlačený plyn |
| Řada | MSQ |
| Další údaje | narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table Air connections of 2 pages possible |



Výrobek

| Označení | Ø pístu (mm) | Přípoj pneumatický systém | Konstrukční velikost | Tlumení | Hmotnost na m (kg) |
|----------------|--------------|---------------------------|----------------------|---|--------------------|
| K- 07 55 01 13 | 6 | M 3 | 1 | without, with adjustment bolt | 0,075 |
| K- 07 55 01 18 | 8 | M 5 | 2 | without, with adjustment bolt | 0,105 |
| K- 07 55 01 21 | 10 | M 5 | 3 | elastic, with adjustment bolt | 0,150 |
| K- 07 55 01 26 | 12 | M 5 | 7 | elastic, with adjustment bolt | 0,250 |
| K- 07 55 01 11 | 15 | M 5 | 10 | elastic, with adjustment bolt | 0,530 |
| K- 07 55 01 16 | 18 | M 5 | 20 | elastic, with adjustment bolt | 0,990 |
| K- 07 55 01 19 | 21 | G 1/8 | 30 | elastic, with adjustment bolt | 1,290 |
| K- 07 55 01 22 | 25 | G 1/8 | 50 | elastic, with adjustment bolt | 2,080 |
| K- 07 55 01 24 | 28 | G 1/8 | 70 | elastic, with adjustment bolt | 2,880 |
| K- 07 55 01 09 | 32 | G 1/8 | 100 | elastic, with adjustment bolt | 4,090 |
| K- 07 55 01 14 | 40 | G 1/8 | 200 | elastic, with adjustment bolt | 7,580 |
| K- 07 55 01 12 | 15 | M 5 | 10 | elastic, with integrated shock absorber | 0,540 |
| K- 07 55 01 17 | 18 | M 5 | 20 | elastic, with integrated shock absorber | 0,990 |
| K- 07 55 01 20 | 21 | G 1/8 | 30 | elastic, with integrated shock absorber | 1,290 |
| K- 07 55 01 23 | 25 | G 1/8 | 50 | elastic, with integrated shock absorber | 2,100 |
| K- 07 55 01 25 | 28 | G 1/8 | 70 | elastic, with integrated shock absorber | 2,880 |
| K- 07 55 01 10 | 32 | G 1/8 | 100 | elastic, with integrated shock absorber | 4,100 |
| K- 07 55 01 15 | 40 | G 1/8 | 200 | elastic, with integrated shock absorber | 7,650 |