

LKM MM ST DK

Hrdlo násuvné spojky (vzduch) s pojistkou

HANSA FLEX

Vlastnosti

Konstrukce	objímka potrubní rychlospojky
Přípoj 1	Hadicová přípojka
Přípoj 2	
Provozní tlak	max. 12 bar
Průtok vzduchu	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Teplota média	-20 °C to +70 °C
Pouzdro	Aluminium, anodised
Závit	Nickel-plated brass
Vnitřní součásti	Stainless steel
Hlava, ventil	Hardened, galvanised steel
Těsnicí materiál	Nitrilkaučuk



Upozornění

Not suitable for hitting / pulsating tools.

Další údaje na dotaz.

Popis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Výrobek

Označení	pro vnitřní průměr hadice (mm)	Přípoj	Délka (mm)	SW (mm)
LKM 06 MM ST DK	6	Stem, I.D. 6	88,5	21
LKM 09 MM ST DK	9	Stem, I.D. 9	88,5	21
LKM 13 MM ST DK	13	Stem, I.D. 13	88,5	21